SecuOne

DoP
VERSION: 1/2026

(DoP: FR-44361)

Declaration of performance

Construction Products Regulation (EU) No 305/2011

1. Product:	SecuOne® pre-tape.
2. Product Identification:	See bar code and label on packaging.
3. Intended Use:	Flexible membranes for waterproofing, EN 13956
4. Manufacturing Locations:	VM Building Solutions NV/SA Europalaan 73 B-9800 Deinze
5. Representative Contact:	N.A.
6. AVCP:	2+
7. Notified Body (hEN):	BCCA Hermeslaan 9, 1831 BE-Diegem Registration No. 0749
8. Notified Body (ETA):	N.A.

SecuOne®

9. Declared Performance:			
Essential Characteristics	**Performance**	**Test standard**	**Harmonised technical specifications**
Effective Thickness	-5% to +10%	EN 1849-2	EN 13956: 2012
External Fire Performance	F_{roof}[1]	EN 13501-5	
Reaction to Fire	E	EN 13501-1	
Joint Peel Resistance (N/50mm)	≥ 25	EN 12316-2	
Joint Shear Resistance (N/50mm)	≥ 200	EN 12317-2	
Tensile (Breaking) Strength (N/50mm)	≥ 400	EN 12311-2	
Elongation (%)	≥ 15	EN 12311-2	
Tear Resistance (N)	≥ 25	EN 12310-1	
Dimensional Stability (%)	≤ 0,5	EN 1107-2	
Flexibility at Low Temperature (°C)	≤ -45	EN 495-5	
UV Exposure	pass	EN 1297	
Resistance to Ozone	pass	EN 1844	
Resistance to Impact (method B) (Classe L)	≥ L20	EN 12730	
Static Puncture (method B) (mm)	≥ 2.000	EN 12691	
Hazardous substances	pass		


1) The roof membranes can be used for a Broof(t1) classification for External Fire Performance for a well-defined full roof assembly. Composition of this roof assembly is available upon request.

10. Declaration:

The performance of the product identified in points 1 and 2 is in conformity with the declared performance in point 9. This Declaration of Performance is issued under the sole responsibility of the manufacturer identified in point 4.

Signed for and on behalf of the manufacturer by:

Sammy Baron



Technical Director
VM Building Solutions NV/SA